

## PENETROX Bottle 8 Ounce

By Burndy  
Catalog # P8A

PENETROX Bottle 8 Ounce



### Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

### Application

Aluminum to Aluminum, Aluminum to Conduit, Aluminum to Copper

### Specifications

Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

### Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Package Height	0.000 in

### General

Sub Brand	PENETROX
Trade Name	PENETROX™
Application - For Use On	<ul style="list-style-type: none"> <li>• Aluminum to Aluminum</li> <li>• Aluminum to Conduit</li> <li>• Aluminum to Copper</li> </ul>
Pour Point	-15 °F
Type	Sealing compound
UPC 12 Digit	781810592557
UPC 14 Digit GTIN	00781810592557
Container Type	Squeeze Bottle
UPC	781810592557

### Logistics

Container Size	8 oz
Carton Quantity	12
Pallet Quantity	1680

### Operational

Temperature - Dropping Point Fahrenheit	230 °F
Viscosity at 100 Fahrenheit	305 °F

### Product Assets

[Catalog \[English\]](#)