BRYANT®

# Locking Devices, Industrial, Female Connector Body, 30A 277V AC, 2-Pole 3-Wire Grounding, L7-30R, Screw Terminal, Black and White



By Bryant
Catalog # 70730NC

Locking Devices, Industrial, Female Connector Body, 30A 277V AC, 2-Pole 3-Wire Grounding, L7-30R, Screw Terminal, Black and White

## Features

- 
- 
- 
- 

## Application

Heavy Duty Industrial

## General

| | |
|---|---|
| Catalog Number | 70730NC |
| Color | Black, White |
| EU RoHS Indicator | Yes |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| Insulation | Insulated Body |
| Item Type | 30A Triple Gripper Nylon Connector |
| Material | Composite |
| Material - Mounting Hardware | Cord Mounted |
| Number Of Poles | 2-Pole |
| OEM Brand Name | Hubbell Bryant |
| Style | Internal Cord Clamp |
| Temperature Rating | Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact, -25° with impact. |
| Type | Connector Body |
| UPC | 781786690295 |

## Dimensions

| | |
|---|---|
| Dimensions | 2.13 in x 2.13 in x 3.90 in |
| Display Size | Standard Sized Product |
| Height | 3.9 in |
| Length | 2.13 in |
| Width | 2.13 in |

## Electrical Ratings

| | |
|---|---|
| Amperage Rating | 30 A |
| Connectivity | Screw Terminals |
| Current Rating | 30 A |
| Voltage Rating | 277 VAC |
| Voltage Rating Description | 277 VAC |

## Conductor Related

| | |
|---|---|
| Conductor Range | #12 AWG to #8 AWG |
| Number Of Wires | 3-Wire |
| Number of Conductors | 3-Wire Grounding |
| Wire Size | #18 AWG to #8 AWG |

## Certifications And Compliance

| | |
|---|---|
| Nema Rating | L7-30R |
| Standards - RoHS Compliance Status | CM |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |

## Product Assets

Catalog Page - BRY H-11 Catalog Page
Catalogs - Bryant Full Line Catalog
Specifications - 70730NC



©2025 Hubbell Incorporated. All rights reserved