ReliaHome three phase load centers

Main lug, factory installed, indoor (NEMA 1) enclosure, top/bottom feed

Main ampere rating	1 pole, 1" spaces	2 pole, 1" spaces	3 pole, 1" spaces	Total 1-pole spaces	Front type	Box number	Main wire size (AWG/kcmil) Cu-Al	Equipment ground kit	Ordering code
125	12	6	4	12	Combination	4	6-2/0	TGK12 (order separately) TGK24 (order separately)	TL12412C
150	18	8	6	18	Combination	7	1-3/0 (Cu), 2/0-3/0 (Al)	TGK24 (order separately) TGK32 (order separately)	TL18415C
	24	12	8	24	Combination	7	1-3/0 (Cu), 2/0-3/0 (Al)	TGK24 (order separately) TGK32 (order separately)	TL24415C



TL12412R

Main lug, factory installed, outdoor (NEMA 3R) enclosure, top feed

Main ampere rating	1 pole, 1" spaces	2 pole, 1" spaces	3 pole, 1" spaces	Total 1-pole spaces	Box number	Main wire size (AWG/kcmil) Cu-Al	Equipment ground kit	Ordering code
125	12	6	4	12	R3	6-2/0	TGK12 or TGK24 (order separately)	TL12412R
150	18	8	6	18	R4	1-3/0 (Cu), 2/0-3/0 (Al)	TGK24 or TGK32 (order separately)	TL18415R
	24	12	8	24	R4	1-3/0 (Cu), 2/0-3/0 (Al)	TGK24 or TGK32 (order separately)	TL24415R



TM42420C

Main circuit breaker, factory installed, indoor (NEMA 1) enclosure

Main ampere rating	1 pole, 1" spaces	2 pole, 1" spaces	3 pole, 1" spaces	Total 1-pole spaces	Front type	Box number	Main wire size (AWG/kcmil) Cu-Al	Equipment ground kit	Ordering code
100	12	6	4	12	Combination	6	6-1/0 (Cu), 4-1/0 (Al)	TGK12 or TGK24 (order separately)	TM12410C
	18	8	6	18	Combination	6	6-1/0 (Cu), 4-1/0 (Al)	TGK24 or TGK32 (order separately)	TM18410C
125	30	14	10	30	Combination	12	1-3/0 (Cu), 2/0-3/0 (Al)	TGK32 (order separately)	TM30412C
150	24	12	8	24	Combination	11	1-3/0 (Cu), 2/0-3/0 (Al)	TGK32 (order separately)	TM24415C
	30	14	10	30	Combination	12	1-3/0 (Cu), 2/0-3/0 (Al)	TGK32 (order separately)	TM30415C
	42	20	14	42	Combination	15	1-3/0 (Cu), 2/0-3/0 (Al)	TGK42 (order separately)	TM42415C
200	24	12	8	24	Combination	12	1-300 (Cu), 2/0-300 (Al)	TGK32 (order separately)	TM24420C
	30	14	10	30	Combination	13	1-250 (Cu), 2/0-250 (Al)	TGK32 (order separately)	TM30420C
	42	20	14	42	Combination	14	1-250 (Cu), 2/0-250 (Al)	TGK42 (order separately)	TM42420C
225	42	20	14	42	Combination	15A	1-300 (Cu), 2/0-300 (Al)	(2) TGL2 (order separately)	TM42422C



TM30420R

Main circuit breaker, factory installed, outdoor (NEMA 3R) enclosure, top feed

Main ampere rating	1 pole, 1" spaces	2 pole, 1" spaces	3 pole, 1" spaces	Total 1-pole spaces	Box number	Main wire size (AWG/kcmil) Cu-Al	Equipment ground kit	Ordering code
100	18	8	6	18	R4	6-1/0 (Cu), 4-1/0 (Al)	TGK24 or TGK32 (order separately)	TM18410R