

YS29LBOX, Compression Splice, 250 kcmil Cu, Standard Barrel

By Burndy

Catalog # [YS29LBOX](#)

250 kcmil, CU, Standard Barrel SPLICE



Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	250 kcmil
Conductor - Copper Str Size	250 kcmil
Conductor - Copper Str Navy Size	250 (61) Navy
Conductor Size	250 KCMIL
Conductor - Copper Str Size Range	250 kcmil
Conductor Type	CODE

Configuration

Connector Type	STANDARD BARREL
----------------	-----------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.75 inch
Dimension - L Length Overall mm	62 mm
Dimension - Strip Length inch	1-1/8
Dimension - B Length fraction	1-1/16 in
Dimension - B Length inch	1.06 in
Dimension - Length Overall inch	2.46 in

General

Die Index	16
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Yellow
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style Type	Chamfered
UPC 12 Digit	781810557006
UPC 14 Digit GTIN	00781810557006
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810557006

Logistics

Minimum Pack Quantity	1
Carton Quantity	6

Product Assets

[Catalog \[English\]](#)