

## YS39L, Compression Splice, 750 kcmil Cu, Standard Barrel

By Burndy  
Catalog # [YS39L](#)

750 kcmil, CU, Standard Barrel SPLICE



### Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

### Application

Wire Splice

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	COPPER
Wire Size	750 kcmil
Conductor - Copper Str Size	750 kcmil
Conductor - Copper Str	750
Compact Size	
Conductor Size	750 KCMIL
Conductor - Copper Str Size	750 kcmil
Range	
Conductor Type	CODE

### Configuration

Connector Type STANDARD BARREL

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - L Length Overall mm	94 mm
Dimension - Strip Length inch	1-11/16
Dimension - B Length fraction	1-5/8 in
Dimension - B Length inch	1.62 in
Dimension - Length Overall inch	3.72 in

### General

Die Index	24
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Black
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YS-L, Standard Barrel
UPC 12 Digit	781810527153
UPC 14 Digit GTIN	00781810527153
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810527153

### Logistics

Minimum Pack Quantity	1
Carton Quantity	6

### Product Assets

[Catalog \[English\]](#)