YGHP34C29 Figura 6 Conector de puesta a tierra por compresión



Por Burndy
No de catálogo YGHP34C29

Conector de varilla de tierra de compresión Cu, 250- 500 kcmil, varilla de 5/8"- 3/4", barra de refuerzo de 5/8" a 3/4" (carrera) a cadena de 3/0 a 250 kcmil (toma)

Características

- Irreversible compression ground tap can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Aplicación

For Direct Burial In Earth And Concrete

Especificaciones

Certification - ETL	No
Certification - UL Recognized	No
Standards - Industry Standards Met	• UL467 • IEEE 837
Standards - RoHS Compliance Status	CM
Certification - cULus	No
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	Direct Burial
UL Listed	Yes
Certification - CSA Approved	Yes

Relacionado con conductores

Conductor - Rebar Run Range	5 -6
Conductor - Rebar Run	• 5 • 6
Conductor - Rod Run Range	5/8 in-3/4 in
Conductor - Rod Run	• 5/8 in • 3/4 in
Conductor - Copper Str Run Range	250 kcmil-500 kcmil
Conductor - Copper Str Run	• 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil
Conductor - Copper Str Tap Range	3/0 AWG-250 kcmil
Conductor - Copper Str Tap	• 3/0 AWG • 4/0 AWG • 250 kcmil

Configuración

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensiones

Package Height	0.000 in
Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - B Length inch	0.75 in

General

Plated	No
Trade Name	HYTAP™
Sub Brand	HYTAP
Die Index	998
Product Type	Compression
Oxide Inhibitor Type	Penetrox E
UPC	781810220979
Type	Taps
Prefilled Oxide Inhibitor	Y
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810220979
UPC 14 Digit GTIN	00781810220979

Logística

Pallet Quantity	5920
Carton Quantity	20

Documentación del producto

Catalog [English]

© 2026 Hubbell Incorporated. Todos los derechos reservados