

YHD400, Line Tap Connector, AL-CU, AL-AL

By Burndy
Catalog # [YHD400](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - ACSR Cmpt Run Range	3/0 AWG-266.8 kcmil
Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG • 266.8 kcmil
Conductor - AL Str Run Range	3/0 AWG-4/0 AWG
Conductor - AL Str Run	<ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG
Conductor - AL Str Tap Range	4/0 AWG
Conductor - AL Str Tap	4/0 AWG
Conductor - ACSR Cmpt Tap Range	3/0 AWG-266.8 kcmil
Conductor - ACSR Cmpt Tap	<ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG • 266.8 kcmil

Conductor - ACSR Str Run Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penquin AWG
Conductor - ACSR Str Run	<ul style="list-style-type: none"> • 3/0 (6/1) Pigeon AWG • 4/0 (6/1) Penquin AWG
Conductor - ACSR Str Tap Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penquin AWG
Conductor - ACSR Str Tap	<ul style="list-style-type: none"> • 3/0 (6/1) Pigeon AWG • 4/0 (6/1) Penquin AWG
Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Run Range	250 - 300
Conductor - Copper Solid Run	250 - 300
Conductor - Copper Solid Tap Range	250-300
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> • 250 • 300
Conductor - Copper Str Tap Range	4/0 AWG
Conductor - Copper Str Tap	4/0 AWG

Dimensions

Package Height	2.800 in
Dimension - Height mm	35.6 mm
Dimension - Height inch	1.40 in
Dimension - Height fraction	1-49/100 in
Package Weight	4.500 lb.
Package Length	13.400 in
Package Width	4.900 in
Dimension - L Length Overall mm	64 mm
Dimension - Width fraction	89/100 in
Dimension - Width mm	21 mm
Dimension - Width inch	0.84 in
Dimension - Length Overall inch	2.50 in

General

Trade Name	HYCRIMP™
Die Index	D3
Prefilled Oxide Inhibitor	Y
Plated	N
Sub Brand	HYCRIMP
UPC	781810139356

Type	YHD	Minimum Pack Quantity	25
Material	Aluminum	Pallet Quantity	3200
Plating Type	Unplated	Carton Quantity	200
UPC 14 Digit GTIN	00781810139356		

Logistics



A Hubbell brand

Product Assets

[Catalog \[English\]](#)

© 2026 Hubbell Incorporated. All rights reserved
BRDY-YHD400-SPEC-EN | REV 5/2026