

## YHD350, Line Tap Connector, AL-CU, AL-AL

By Burndy  
Catalog # [YHD350](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range, groove A(Run):0.461-0.563

### Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

### Application

For Copper, Aluminum Or ACSR And Compact Conductors

### Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

### Conductor

Conductor - ACSR Cmpt Run Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> </ul>
Conductor - AL Str Run Range	3/0-4/0
Conductor - AL Str Run	3/0-4/0
Conductor - AL Str Tap Range	2/0 AWG-3/0 AWG
Conductor - AL Str Tap	<ul style="list-style-type: none"> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> </ul>
Conductor - ACSR Cmpt Tap Range	1 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	<ul style="list-style-type: none"> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 3/0 AWG</li> <li>• 2/0 AWG</li> </ul>

Conductor - ACSR Str Run Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penquin AWG
Conductor - ACSR Str Run	<ul style="list-style-type: none"> <li>• 3/0 (6/1) Pigeon AWG</li> <li>• 4/0 (6/1) Penquin AWG</li> </ul>
Conductor - ACSR Str Tap Range	1 (6/1) Robin AWG-2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap	<ul style="list-style-type: none"> <li>• 1 (6/1) Robin AWG</li> <li>• 1/0 (6/1) Raven AWG</li> <li>• 2/0 (6/1) Quail AWG</li> </ul>
Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> </ul>
Conductor - Copper Solid Run Range	250 - 300
Conductor - Copper Solid Run	250 - 300
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> </ul>
Conductor - Copper Str Tap Range	1 AWG-2/0 AWG
Conductor - Copper Str Tap	<ul style="list-style-type: none"> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> </ul>

### Dimensions

Package Height	2.750 in
Dimension - Height mm	36.1 mm
Dimension - Height inch	1.42 in
Dimension - Height fraction	1-21/50 in
Package Weight	4.450 lb.
Package Length	13.300 in
Package Width	4.750 in
Dimension - L Length Overall mm	57 mm
Dimension - Width fraction	89/100 in
Dimension - Width mm	23 mm
Dimension - Width inch	0.89 in
Dimension - Length Overall inch	2.25 in

### General

Trade Name	HYCRIMP™
Die Index	D3
Prefilled Oxide Inhibitor	Y

Plated	N
Sub Brand	HYCRIMP
UPC	781810139301
Type	YHD
Material	Aluminum
Plating Type	Unplated
UPC 14 Digit GTIN	00781810139301

### Logistics

Minimum Pack Quantity	25
Pallet Quantity	3200
Carton Quantity	200

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand