

# YHD200, Compression Line Tap, CU, AL, ACSR, Compact

By Burndy  
 Catalog # [YHD200](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range, groove A(Run):0.398-0.470

## Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

## Application

For Copper, Aluminum Or ACSR And Compact Conductors

## Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

## Conductor

Conductor - ACSR Cmpt Run Range	2/0 AWG-3/0 AWG
Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> </ul>
Conductor - AL Str Run Range	3/0 - 4/0
Conductor - AL Str Run	3/0 - 4/0
Conductor - AL Str Tap Range	6 AWG-1 AWG
Conductor - AL Str Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>
Conductor - ACSR Cmpt Tap Range	6 AWG-1 AWG
Conductor - ACSR Cmpt Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 4 AWG</li> </ul>

Conductor - ACSR Str Run Range	<ul style="list-style-type: none"> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>
Conductor - ACSR Str Run	1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap Range	<ul style="list-style-type: none"> <li>• 1/0 (6/1) Raven AWG</li> <li>• 2/0 (6/1) Quail AWG</li> </ul>
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - Copper Str Run Range	<ul style="list-style-type: none"> <li>• 6 (6/1) Turkey AWG</li> <li>• 5 (6/1) Thrush AWG</li> <li>• 4 (6/1) Swan AWG</li> <li>• 4 (7/1) Swanate AWG</li> <li>• 3 (6/1) Swallow AWG</li> <li>• 2 (6/1) Sparrow AWG</li> <li>• 2 (7/1) Sparate AWG</li> </ul>
Conductor - Copper Str Run	2/0 AWG-3/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> </ul>
Conductor - Copper Solid Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Solid Run	<ul style="list-style-type: none"> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> </ul>
Conductor - Copper Solid Tap Range	6 AWG-1/0 AWG
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>
Conductor - Copper Str Tap Range	6 AWG-1 AWG
Conductor - Copper Str Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>

## Dimensions

Package Height	0.000 in
Dimension - Height mm	36.8 mm
Dimension - Height inch	1.45 in

Dimension - Height fraction 1-11/25 in  
Package Weight 0.000 lb.  
Package Length 0.000 in  
Package Width 0.000 in  
Dimension - L Length Overall 41 mm  
mm  
Dimension - Width mm 23 mm  
Dimension - Width inch 0.89 in  
Dimension - Length Overall 1.62 in  
inch

### General

Trade Name HYCRIMP™  
Die Index D3  
Prefilled Oxide Inhibitor Y

Plated N  
Sub Brand HYCRIMP  
UPC 781810139158  
Type YHD  
Material Aluminum  
Plating Type Unplated  
UPC 14 Digit GTIN 00781810139158

### Logistics

Minimum Pack Quantity 25  
Pallet Quantity 8250  
Carton Quantity 250

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand