

# YHO150, Aluminum Overhead Tap Connector, AL, CU, ACSR, AAAC, Steel

By Burndy  
Catalog # [YHO150](#)



AL Overhead Compression Tap Connector, Accommodates: AL, CU, ACSR, AAAC and Steel, Length: 1.50 IN

## Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

## Application

For Copper, Aluminum Or ACSR And Compact Conductors

## Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

## Conductor

Conductor - ACSR Cmpt Run Range	2 AWG-1/0 AWG
Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> </ul>
Conductor - AL Str Run Range	#1 - 2/0
Conductor - AL Str Run	#1 - 2/0
Conductor - AL Str Tap Range	6 AWG-1 AWG
Conductor - AL Str Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>
Conductor - ACSR Cmpt Tap Range	6 AWG-1 AWG
Conductor - ACSR Cmpt Tap	• 6 AWG

Conductor - ACSR Str Run Range	<ul style="list-style-type: none"> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> </ul>
Conductor - ACSR Str Run	3 (6/1) Swallow AWG-1/0 (6/1) Raven AWG
Conductor - ACSR Str Tap Range	<ul style="list-style-type: none"> <li>• 3 (6/1) Swallow AWG</li> <li>• 2 (6/1) Sparrow AWG</li> <li>• 2 (7/1) Sparate AWG</li> <li>• 1 (6/1) Robin AWG</li> <li>• 1/0 (6/1) Raven AWG</li> </ul>
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - Copper Str Run Range	<ul style="list-style-type: none"> <li>• 6 (6/1) Turkey AWG</li> <li>• 5 (6/1) Thrush AWG</li> <li>• 4 (6/1) Swan AWG</li> <li>• 4 (7/1) Swanate AWG</li> <li>• 3 (6/1) Swallow AWG</li> <li>• 2 (6/1) Sparrow AWG</li> <li>• 2 (7/1) Sparate AWG</li> </ul>
Conductor - Copper Str Run	3 AWG-2/0 AWG
Conductor - Copper Str Tap Range	<ul style="list-style-type: none"> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> </ul>
Conductor - Copper Solid Run Range	1 AWG-2/0 AWG
Conductor - Copper Solid Run	<ul style="list-style-type: none"> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> </ul>
Conductor - Copper Solid Tap Range	6 AWG-1/0 AWG
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> </ul>
Conductor - Copper Str Tap Range	6 AWG-1 AWG
Conductor - Copper Str Tap	<ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul>

- 2 AWG
- 1 AWG

### Dimensions

Package Height	0.000 in
Dimension - Height mm	28.7 mm
Dimension - Height inch	1.13 in
Dimension - Height fraction	1-3/25 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	38 mm
Dimension - Width fraction	7/10 in
Dimension - Width mm	18 mm
Dimension - Width inch	0.70 in
Dimension - Length Overall inch	1.50 in

Trade Name	HYCRIMP™
Die Index	O
Prefilled Oxide Inhibitor	Y
Plated	N
Sub Brand	HYCRIMP
UPC	781810139103
Type	YHO
Material	Aluminum
Plating Type	Unplated
UPC 14 Digit GTIN	00781810139103

### Logistics

Minimum Pack Quantity	25
Pallet Quantity	11550
Carton Quantity	350

### Product Assets

[Catalog \[English\]](#)

### General



A Hubbell brand