

YHO100, Aluminum Overhead Tap Connector, AL, CU, ACSR, AAAC, Steel

By Burndy
Catalog # [YHO100](#)



AL Overhead Compression Tap Connector, Accommodates: AL, CU, ACSR, AAAC and Steel, Length: 1.25 IN

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - ACSR Cmpt Run Range	#6-#1
Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> • #6 • 4 AWG • 3 AWG • #1
Conductor - AL Str Run Range	#6 - #1
Conductor - AL Str Run	#6 - #1
Conductor - AL Str Tap Range	6 AWG-1 AWG
Conductor - AL Str Tap	<ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - ACSR Cmpt Tap Range	6 AWG-3 AWG
Conductor - ACSR Cmpt Tap	<ul style="list-style-type: none"> • 6 AWG • 4 AWG

Conductor - ACSR Str Run Range	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 3 AWG
Conductor - ACSR Str Run	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - ACSR Str Tap Range	<ul style="list-style-type: none"> • 6 (6/1) Turkey AWG • 5 (6/1) Thrush AWG • 4 (6/1) Swan AWG • 4 (7/1) Swanate AWG • 3 (6/1) Swallow AWG • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - Copper Str Run Range	<ul style="list-style-type: none"> • 6 (6/1) Turkey AWG • 5 (6/1) Thrush AWG • 4 (6/1) Swan AWG • 4 (7/1) Swanate AWG • 3 (6/1) Swallow AWG • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG
Conductor - Copper Str Run	6 AWG-1 AWG
Conductor - Copper Solid Run Range	<ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - Copper Solid Run	6 AWG-1 AWG
Conductor - Copper Solid Tap Range	<ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - Copper Solid Tap	6 AWG-1 AWG
Conductor - Copper Str Tap Range	<ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - Copper Str Tap	6 AWG-1 AWG

- Conductor - Copper Str Tap
- 6 AWG
 - 5 AWG
 - 4 AWG
 - 3 AWG
 - 2 AWG
 - 1 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	28.4 mm
Dimension - Height inch	1.12 in
Dimension - Height fraction	1-3/25 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	32 mm
Dimension - Width fraction	7/10 in
Dimension - Width mm	18 mm
Dimension - Width inch	0.70 in
Dimension - Length Overall inch	1.25 in

General

Trade Name	HYCRIMP™
Die Index	O
Prefilled Oxide Inhibitor	Y
Plated	N
Sub Brand	HYCRIMP
UPC	781810139004
Type	YHO
Material	Aluminum
Plating Type	Unplated
UPC 14 Digit GTIN	00781810139004

Logistics

Minimum Pack Quantity	25
Pallet Quantity	11550
Carton Quantity	350

Product Assets

[Catalog \[English\]](#)



A Hubbell brand