Specifications



Eaton DH361URK

Eaton Heavy duty single-throw non-fused safety switch, Single-throw, 30 A, NEMA 3R, Painted galvanized steel, Non-Fusible, Three-pole, 5 at 250 Vdc, Three-wire, 7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph

General specifications	
PRODUCT NAME	Eaton heavy duty non-fusible safety switch
CATALOG NUMBER	DH361URK
UPC	782113205519
PRODUCT LENGTH/DEPTH	9.89 in
PRODUCT HEIGHT	15.81 in
PRODUCT WIDTH	8.87 in
PRODUCT WEIGHT	16 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEC 230.62 (C) Compliant Barrier
CERTIFICATIONS	UL Listed
CATALOG NOTES	Suitable for service entrance use with a neutral or ground lug kit installed
PRODUCT TYPE	Non-fusible safety switch

Powering Business Worldwide

Physical Attributes

ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Non-fusible
NUMBER OF POLES	Three-pole
NUMBER OF WIRES	3
TYPE	Single-throw

Performance Ratings

AMPERAGE RATING	30A
HP RATING - MAX	7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc
NEMA RATING	NEMA 3R
VOLTAGE RATING	600 V

Miscellaneous

PRODUCT CATEGORY	Heavy Duty, Non-Fusible

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DH361URK

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.