



XCS-0B4 - XCS Series, AL Momentary Contact Double Push Button Cvr w/ Device, Green Button w/ Start Nameplate, Red Button w/ Stop Nameplate, 1NO/1NC

By Killark
Catalog # XCS-0B4



XCS Series - Aluminum Momentary Contact Double Push Button Cover With Device - Green Button With "Start" Nameplate - Red Button With "Stop" Nameplate - 1NO/1NC Contact Rating

Features

- Copper free cast aluminum alloy.
- Ground flange joint between bolted cover and box provide required flame path.
- Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where simi

Specifications

Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer
UL File Number	E53360
CSA File Number	LR11714
Buy America(n) Qualified	Contact Manufacturer

Conductor

Number Of Poles 2

Configuration

Back Box Type SWB

Current

Contact Rating • 60A INRUSH @ 120 VAC

- 30A INRUSH @ 240 VAC
- 15A INRUSH @ 480 VAC
- 12A INRUSH @ 600 VAC
- 6A BREAKING @ 120 VAC
- 3A BREAKING @ 240 VAC
- 1.5A BREAKING @ 480 VAC
- 1.2A BREAKING @ 600 VAC
- 10A CARRYING @ 120 VAC
- 10A CARRYING @ 240 VAC
- 10A CARRYING @ 480 VAC

Amperage Rating 10 A
Frequency Rating 50/60 Hz

Dimensions

Gross Weight with Packaging 1.33
Depth 1-3/4
Width 6 in
Height 4.375 in
Length 6.375 in
Dimensions 6.375 in x 6 in x 4.375 in

General

Type Aluminum Cover With Two Push Buttons
Series XCS Series
Material Copper-free aluminum
UPC 783936890081
Color Green-Red

Operational

Action SP (per circuit)
Actuator Momentary Pushbutton

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[French, English\]](#)