



# XCS-OMMR3 - XCS Series, AL Maintained Contact Push/Pull Button Cvr w/ Device, Red Mushroom w/ 3 Nameplates Start/Stop, Blank, Emergency Stop, 1NO/1NC

By Killark  
Catalog # XCS-OMMR3



XCS Series - Aluminum Maintained Contact Push/Pull Button Cover With Device - Red Mushroom Button Supplied With Three Nameplates("Start/Stop", Blank, "Emergency Stop") - 1NO/1NC Contact Rating

## Features

- Copper free cast aluminum alloy.
- Ground flange joint between bolted cover and box provide required flame path.
- Push button, selector switches and pilot light operator bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

## Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where simi

## Specifications

EU RoHS Indicator	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	<ul style="list-style-type: none"> <li>• Class I, Divisions 1 &amp; 2, Groups C, D</li> <li>• Class I, Zones 1 &amp; 2, Groups IIB, IIA</li> <li>• Class II, Divisions 1 &amp; 2, Groups E, F, G</li> <li>• Class III, Divisions 1 &amp; 2</li> </ul>
UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer

## Conductor

Number Of Poles	1
-----------------	---

## Configuration

Back Box Type	SWB
---------------	-----

## Current

Amperage Rating	10 A
Frequency Rating	50/60 Hz

## Contact Rating

- 60A INRUSH @ 120 VAC
- 30A INRUSH @ 240 VAC
- 15A INRUSH @ 480 VAC
- 12A INRUSH @ 600 VAC
- 6A BREAKING @ 120 VAC
- 3A BREAKING @ 240 VAC
- 1.5A BREAKING @ 480 VAC
- 1.2A BREAKING @ 600 VAC
- 10A CARRYING @ 120 VAC
- 10A CARRYING @ 240 VAC
- 10A CARRYING @ 480 VAC

## Dimensions

Depth	3-1/8
Length	5.56 in
Gross Weight with Packaging	1.4
Width	4 in
Height	5.63 in
Dimensions	5.56 in x 4 in x 5.63 in

## General

Series	XCS Series
Color	Red
Type	Aluminum Cover With Push-Pull Button
Material	Copper-free aluminum
UPC	783936890401

## Logistics

Carton Quantity	5
-----------------	---

## Operational

Action	SP
Actuator	Maintained Pushbutton

## Product Assets

[Catalog \[English\]](#)

