BURNDY

Conector C-TAP de conexión a tierra por compresión YGHC34C29



Por Burndy
No de catálogo YGHC34C29

Conector C de compresión de cobre, 300-500 kcmil (Run) y 3/0 AWG (Str) - 250 kcmil (Tap)

Características

- Irreversible compression ground tap figure C connector
- C-shaped opening permits placing two continuous parallel cables into conductor groove
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Aplicación

For Direct Burial Cables

Especificaciones

Certification - ETL	No
Certification - UL Recognized	No
Standards - Industry Standards Met	• UL467 • IEEE 837 • UL468A-468B
Standards - RoHS Compliance Status	CM
Certification - cULus	No
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	Direct Burial
UL Listed	Yes
Certification - CSA Approved	Yes

Relacionado con conductores

Conductor - Copper Str Run Range	300 kcmil-500 kcmil
Conductor - Copper Str Run	• 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil
Conductor - Copper Str Tap Range	3/0 AWG-250 kcmil
Conductor - Copper Str Tap	• 3/0 AWG • 4/0 AWG • 250 kcmil

Configuración

Physical Attribute - Number of Crimps Required	2
Connector Type	Tap

Dimensiones

Package Height	0.000 in
Dimension - Height mm	67.8 mm
Dimension - Height inch	2.67 in
Dimension - Height fraction	2-2/3 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	22 mm
Dimension - B Length inch	0.88 in
Dimension - Length Overall inch	0.88 in

General

Plated	No
Product Family	Grounding and Bonding Connectors>"Hyground" Compression Grounding Connectors>C-Taps
Trade Name	HYTAP™
Sub Brand	HYGROUND, HYTAP
Die Index	1011
Product Type	Compression
UPC	781810221075
Type	Taps
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810221075
UPC 14 Digit GTIN	00781810221075

Documentación del producto

Catalog [English]

© 2026 Hubbell Incorporated. Todos los derechos reservados