
YGHP2C2 Figura 6 Conector de puesta a tierra por compresión



Por Burndy
No de catálogo YGHP2C2

Conector de derivación de varilla de tierra de compresión irreversible de cobre de alta resistencia

Características

- Irreversible compression ground tap can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Aplicación

For Direct Burial In Earth And Concrete

Especificaciones

Certification - ETL	No
Certification - UL Recognized	No
Standards - Industry Standards Met	• UL467 • IEEE 837 • IEEE 837 2014 Qualified
Standards - RoHS Compliance Status	CM
Certification - cULus	No
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	Direct Burial
UL Listed	Yes
Certification - CSA Approved	Yes

Relacionado con conductores

Conductor - Copper Str Run Range	6-2
Conductor - Copper Str Run	• 6 • 5 • 4 • 3 • 2
Conductor - Copper Solid Run Range	6
Conductor - Copper Solid Run	6
Conductor - Copper Solid Tap Range	6
Conductor - Copper Solid Tap	6
Conductor - Copper Str Tap Range	6-2
Conductor - Copper Str Tap	• 6 • 5 • 4 • 3 • 2

Configuración

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensiones

Package Height	0.000 in
Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - B Length inch	0.75 in

General

Plated	No
Trade Name	HYTAP™
Sub Brand	HYTAP
Die Index	O
Product Type	Compression
Oxide Inhibitor Type	Penetrox E
UPC	781810220917
Type	Taps
Prefilled Oxide Inhibitor	Y
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810220917
UPC 14 Digit GTIN	00781810220917

Logística

Pallet Quantity	17400
Carton Quantity	50

Documentación del producto

Catalog [English]

© 2026 Hubbell Incorporated. Todos los derechos reservados