




## KA34U, AL Universal Terminal, 1-Hole, 3/8" Stud, Dual Rated

By Burndy  
Catalog # [KA34U](#)

Aluminum Universal Terminal, 1 Hole, 4 AWG (Str)-500 kcmil,  
3/8" Stud, 1 Screw, Al/Cu Rated, Tin Plated



### Features

- Dual Rated Panelboard Lugs
- High strength extruded aluminum alloy
- Electro tin-plated for low contact resistance
- Rated to 35kV

### Application

For Aluminum And Copper Conductors

### Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

### Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> <li>• 266 kcmil</li> <li>• 300 kcmil</li> <li>• 336 kcmil</li> <li>• 350 kcmil</li> <li>• 397 kcmil</li> <li>• 400 kcmil</li> <li>• 450 kcmil</li> <li>• 477 kcmil</li> <li>• 500 kcmil</li> </ul>
Conductor - AL Str Size Range	4 AWG-500 kcmil
Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>

- 1 AWG
- 1/0
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil
- 400 kcmil
- 450 kcmil
- 500 kcmil

Conductor Size	4 AWG-500 KCMIL
Number Of Conductors	1
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Str-Size</li> <li>• AL C Str-Size</li> </ul>
Conductor - Copper Str Size Range	4 AWG-500 kcmil

### Configuration

Physical Attribute - Number of Screws	1
Physical Attribute - Number of Holes	1
Connector Type	Terminal

### Dimensions

Dimension - Pad Width inch	1.52 in
Package Height	2.300 in
Dimension - Height mm	40.1 mm
Dimension - Height inch	1.58 in
Dimension - Height fraction	1.58 in
Package Weight	3.670 lb.
Package Length	10.250 in
Package Width	3.550 in
Dimension - L Length Overall mm	71 mm
Dimension - Width fraction	1-51/100 in
Dimension - Hole Size mm	11 mm
Dimension - Hole Size inch	0.42 in
Dimension - Stud Size inch	3/8
Dimension - Bolt Hole Size inch	0.38 in
Dimension - Bolt Size fraction	3/8
Dimension - Width mm	38 mm
Dimension - Width inch	1.51 in
Dimension - D inch	1.50 in
Dimension - N inch	0.88 in

Dimension - Length Overall  
inch 2.81 in

**Force Related**

Installation Torque  
Recommended in-lb 450

**General**

Material - Hardware Aluminum  
Physical Attribute - Screw Type Allen  
Plated Y  
Sub Brand UNIVERSAL TERM  
UPC 781810370247  
Type Bolted Lugs & Terminals

Material Aluminum  
Plating Type Tin  
UPC 14 Digit GTIN 00781810370247

**Logistics**

Minimum Pack Quantity 12  
Pallet Quantity 4608  
Carton Quantity 120

**Operational**

Temperature Rating 194

**Product Assets**

[Catalog \[English\]](#)



A Hubbell brand